



KLQ6119LG

HIGER LABOUR BUS

The Buses are designed specifically to suit shuttle service and staff transport in comfort and safety. Designed and built on semi-Monocoque chassis, assuring highest performance and reliability in its class and suiting corporate budgets.

HIGER LABOUR COACH
TECHNICAL SPECIFICATIONS - KLQ6119LG

Overall Dimension	
L x W x H	10740×2550×3320 mm
wheelbase	5420 mm
B. Performance Specification	
Manufacturer's Max. Total Mass	15000 kg
Complete Vehicle Curb Mass	10500 kg
Seats No.	60+1[one door]
C. Engine Specification	
Engine Model	YC6J200-30
Cylinder Number	6 cylinders
Engine Displacement	6.5L
Max. Power	147/2500
Max. Torque	730/1200~1700
Emission Standard	Euro III
D. Chassis	
Clutch	Diaphragm Spring Clutch
Gearbox	Qj Manual Transmission
Retarder & Abs	No Retarder; Abs
Front Axle	Front Drum Axle
Rear Axle	Rear Drum Axle
Suspension System	Leaf Spring
Steering System	Power Steering
Tyre & Wheel	11R22.5 Tubeless Tyre
E. Body	
Air Conditioner	HIGER roof mounted A/C (24000 KA)
Heater System	No heater
Audio-Visal System	Radio
Luggage Rack	Both sides of luggage racks
Seats	60+1, fixed installed passenger seats, seat layout 3+2
Floor	Grey leatheroid floor
Passenger Door	One pneumatic out-swing passenger door
Window	Sliding windows, single glass
Emergency Roof Exit	Two emergency roof exits
Others	High position brake lamps; dashboard; manual sun visor for driver; safety door (emergency exit)


K H F AUTOMOTIVE TRADING L.L.C.