





KLQ6119TB-S90

HIGER STAFF COACH

The coaches are designed specifically to suit shuttle service and staff transport in comfort and safety. Designed and built on semi-Monocoque chassis, assuring highest performance and reliability in its class and suiting corporate budgets.





HIGER STAFF COACH

Overall Dimension

TECHNICAL SPECIFICATIONS - KLQ6119T B - S90

Overall Dimension	
LXWXH	10740 X 2500 x 3400 mm
Wheelbase	5420 Mm
B. Performance Specification	
Manufacturer's Max. Total Mass	15000 Kg
Complete Vehicle Curb Mass	10500 Kg
Seats No.	49+1+1 [One door]
C. Engine Specification	
Engine Model	Isde 245 30
Cylinder Number	6 Cylinders
Engine Displacement	6.7L
Max. Power	245 Hp
Max. Torque	925N°m/1400rpm
D. Chassis	
Clutch	Diaphragm spring clutch
Gearbox	Fast manual transmission
Retarder & Abs	No retarder; wabco abs
Front Axle	Front drum axle
Rear Axle	Rear drum axle
Suspension System	Leaf spring suspension
Steering System	Power steering
Tyre & Wheel	11R22.5 Tubeless tyre
Others	Automatic slack adjuster; automatic fire extinguish in engine compartment
E. Body	
Air Conditioner	Higer roof mounted a/c [bock compressor, 26000kcal/h]
Heater System	No heater
Audio-Visal System	Radio
Bus Reverse Monitor	Color reverse monitor
Digital Clock	Digital clock
Lighting System	Luxury reading lamp, ceiling lamp, step lamp, high position brake lamp
Curtains For Side Window	Light grey curtain
Luggage Rack	No luggage rack
Seats	45+1+1,Fixed installed passenger seats; 3-points seat belt for exposure passengers; high backrest driver seat.
Floor	Floor anti-attrition leatheroid
Passenger Door	One pneumatic out-swing passenger door with remote control, lock.
Window	Sliding windows, single glass, light grey color
Emergency Roof Exit	Two emergency roof exits
Rear-View	Electric rear-view mirror
Others	First aid kit; fire extinguisher; luxury dashboard; manual sun visor for driver; dual circuit service braking; energy storage spring parking brake;









K H F AUTOMOTIVE TRADING L.L.C.